

SAFE WORK PROCEDURES FLOOR SANDER

SPECIAL INSTRUCTIONS: Persons using a floor sander must only use the machine in accordance with the manufacturer's operating instructions.

Task sequence	Identified hazards in task	Key processes to be followed	Precautions / PPE required
1. General precautions	Electric shock	Sander and leads must be tested and a current test tag attached at plug end.	Do not use if out of test.
		Regularly inspect full length of lead for cuts or crushing damage.	Do not use faulty lead.
		Always use electrical tools on a circuit protected by RCD or safety switch.	Do not use on unprotected circuit.
	Unauthorised entry	Ensure that area to be worked on is secured from unauthorised entry.	Post "no entry" signs at entrances.
2. Pre-start checks	Accidental operation	Unplug machine before inspection, cleaning or maintenance.	
	Faulty or missing parts	Inspect all casings and housings for faults, loose or missing screws, etc.	Replace or repair faulty parts.
	Loss of control	Ensure that all controls operate correctly and turn off when released.	Do not use if faulty.
	Damage to machine	Check floor to be sanded for nails or other obstructions.	Punch nails before sanding.
	Cuts from sharp edges	Ensure that correct belt is fitted and correctly adjusted for task to be done.	Wear gloves when handling sharp
		Inspect belt, and replace if torn, worn or damaged.	objects.
		Ensure that dust collector bag is securely fitted, and not torn or damaged.	
3. Handling and transport	Over-exertion/strain injury	Tilt machine back to keep sanding drum above floor surface when moving.	
		Obtain assistance to load and unload machine when access is difficult.	Observe correct handling practice.
		Ensure that machine is securely restrained from movement for transporting.	
4. Operation	Accidental movement	Follow manufacturer's instructions when using floor sander.	Wear eye and hearing protection
	Over-exertion/strain injury	Use legs to move machine – do not force by using arms and shoulders only.	Observe correct handling practice.
	Harmful exposures	Avoid breathing dust – wear suitable dust mask or respirator in dusty areas.	Wear P1 particulate dust mask.
5. Cleaning and	Moving parts	Disconnect machine from power supply before working on sander.	Unplug machine before work.
maintenance		Remove built up residue from sander drum and rollers, and inside of	Wear cut-resistant gloves.
	Harmful exposure	housing. Avoid breathing dust.	Wear P1 particulate dust mask.
	Electric shock	Avoid water entry into electric motor when washing exterior of machine.	Wipe down - do not hose down.

PRECAUTIONS: The following precautions are to be observed in areas where these procedures are carried out.General precautions		Cleaning and maintenance	
--	--	--------------------------	--